



Shenzhen Absen Optoelectronic Co., Ltd.

A2715 Plus-Specifications

Version: V20190313

	Parameter	Value
Physical Parameter	LED Type	black SMD 1010
	Pixel Pitch (mm)	1.58
	Panel Dimensions (WxHxD)/(mm)	610X343X49
	Pixel Per Panel	384X216
	Panel Weight (kg)	6
	Panel Material	Aluminium
	Module Dimensions (WxH)/(mm)	152.5X343
Optoelectronic Parameter	Brightness (nit)	600
	Refresh Rate (Hz)	1920
	Gray scale (bit)	14
	Contrast Ratio	4000:1
	Color Temperature (K)	6500
	Viewing Angle (H/V) (°)	160/140
	Driving Type	1/48
	AC Operating Voltage (V)	100~240
	Power Consumption (Max./Avg.)(W/m ²)	610/203
	Application Parameter	Storage Temperature (°C)
Operating Temperature (°C)		- 10~ + 40
Storage Humidity (RH)		10% ~85%
Operating Humidity (RH)		10% ~80%
IP Rating (Front/Rear)		IP40/IP21
LED Lifetime (H)		100000
Module Maintenance		Front
PSU & Others Maintenance		Front
Panel Installation Type		Stack, Front/Rear Installation
Certificate		TUV-CE+RoHS/ETL+FCC/CCC

Remark :Power consumption tolerance: ±15%, according to the actual situation.