



Shenzhen Absen Optoelectronic Co., Ltd.

A0421 -Preliminary Specifications

Version : V20210313

Parameter		Value
Physical Parameter	LED Type	SMD 3in1 1921
	Pixel Pitch (mm)	4.44
	Panel Dimensions (WxHxD)/(mm)	1280x960x72
	Pixel Per Panel	288x216
	Panel Weight (kg)	31.5
	Panel Material	Aluminum Profile
	Module Dimensions (WxH)/(mm)	320x320
Optoelectronic Parameter	Brightness (nit)	7500
	Refresh Rate (Hz)	≥3840
	Gray scale (Bit)	16
	Contrast Ratio	14000 : 1
	Color Temperature (K)	6500
	Viewing Angle (H/V) (°)	160/80
	Driving Type	1/9
	AC Operating Voltage (V)	100 ~ 240
	Power Consumption (Max./Avg.)(W/m ²)	580/193
Application Parameter	Storage Temperature (°C)	-40 ~ +60
	Operating Temperature (°C)	-40 ~ +50
	Storage Humidity (RH)	10% ~ 90%
	Operating Humidity (RH)	10% ~ 90%
	IP Rating (Front/Rear)	IP65/IP54
	Module Maintenance	Front
	PSU & Others Maintenance	Front
	Panel Installation Type	Fixed
	Max Rigging QTY.	/
	Certificate	CE,FCC,CCC

Remark:Power consumption tolerance: ±15%, according to the actual situation.